TPM-30 Instruction

Technical parameter:

- Temperature measuring range: －50℃～＋70℃
- Resolution: ＞-20℃, 0.1℃; ≤-20℃, 1℃
- Power supply: 1.5V

Use Description:

- Open the battery cover, put into one button battery. Please notice on the polarity, do not mistake. Display temperature immediately when install the battery.
- Display H℃ when ≥70℃; Display L℃ when ≤ －50℃(in temperature measuring state)

TPM-30 Instruction

Technical parameter:

- Temperature measuring range: －50℃～＋70℃
- Resolution: ＞-20℃, 0.1℃; ≤-20℃, 1℃
- Power supply: 1.5V

Use Description:

- Open the battery cover, put into one button battery. Please notice on the polarity, do not mistake. Display temperature immediately when install the battery.
- Display H℃ when ≥70℃; Display L℃ when ≤ －50℃(in temperature measuring state)

TPM-30 Instruction

Technical parameter:

- Temperature measuring range: －50℃～＋70℃
- Resolution: ＞-20℃, 0.1℃; ≤-20℃, 1℃
- Power supply: 1.5V

Use Description:

- Open the battery cover, put into one button battery. Please notice on the polarity, do not mistake. Display temperature immediately when install the battery.
- Display H℃ when ≥70℃; Display L℃ when ≤ －50℃(in temperature measuring state)

TPM-30 Instruction

Technical parameter:

- Temperature measuring range: －50℃～＋70℃
- Resolution: ＞-20℃, 0.1℃; ≤-20℃, 1℃
- Power supply: 1.5V

Use Description:

- Open the battery cover, put into one button battery. Please notice on the polarity, do not mistake. Display temperature immediately when install the battery.
- Display H℃ when ≥70℃; Display L℃ when ≤ －50℃(in temperature measuring state)