

## Digital Thermometer WT-3

WT-3 digital temperature measuring instrument has lengthened probe and sensor with ventilating cover protection. Specially designed sensor and circuit make temperature measuring faster and more precise. Memorize the present and alarming temperatures. Alarm when exceeds the temperature limits. WT-3 is really a portable temperature measuring instrument with high performance and low price, which can be specially used for temperature measuring when install and maintain in HVAC/R industry, also in car air conditioner, house air conditioner, super market and home.

### Features:

- ◆ Specially designed sensor makes temperature measuring faster
- ◆ Temperature measuring, display in °C or °F
- ◆ Data holding
- ◆ Max./ Min. measuring temperature memory
- ◆ Alarm when exceeding the temperature limits

### Technical parameters:

- ◆ Temperature measuring range: -50°C ~ +120°C (-58°F ~ +248°F)
- ◆ Resolution: 0.1°C
- ◆ Accuracy: ±1°C (-20°C ~ +60°C), ±2.5°C (other range)
- ◆ Power supply: DC1.5V, 7# Alkaline battery

### Operation descriptions

- ◆ [ON/OFF]: LCD displays 25.0°C after it turns on 1 sec. then displays measuring temperature value.
- ◆ [C/F]: Switch between °C and °F.
- ◆ [MAX/MIN]: Display the Max. and Min. memorized temperature value.  
High/Low alarming temperature: Press "SET" to enter into alarm setting mode.  
High alarming temperature flashes. Press [ADL] to add 1°C and add it faster when pressing the key for more than 2 sec. The temperature returns to be 1°C higher than the low alarming temperature when exceeds 200°C. Press OK to save and enter into low alarming temperature setting. Adjust it as the same way. "⏏" displays in alarming mode. Alarm sound lasts for 5 sec. and can be cancelled by press "AC".  
The system will exit to temperature measuring mode if no key operation in 10 sec.
- ◆ [AC]: Cancel alarm and enter into temperature measuring mode. "⏏" disappears.

						WT-3英文 说明书(常规)			JY-8.805.244-3	
标记	处数	分区	更改文件号	签名	年月日	阶段标记	重量	比例	徐州精英电器技术有限公司	
设计			标准化							
校准			版本	V1.0						
审核										
工艺			批准			S	A	-	1: 1	
						共 1 张		第 1 张		